

BRADFORD WHITE  
**POWERSTOR SERIES**<sup>®</sup>  
SINGLE WALL INDIRECT WATER HEATERS



PowerStor Single-Wall models do not use gas, oil or electricity to directly heat potable water. Instead, heating fluid from a boiler passes through the heat exchanger, indirectly heating the surrounding potable water. This produces high volume hot water for many residential applications.

- Six tank sizes: 30, 38, 48, 60, 75 and 116 gallon capacities.
- 1½" O.D. single-wall, glass-coated (Vitraglas<sup>™</sup>), carbon steel heat exchange coil.
- Over 14.2 sq. ft. of heat exchanger surface area.
- Pressure drop is less than 0.65 psi (1.5 ft of head loss) with a flow rate as high as 13.7 gpm.
- 1" female NPT boiler connections are located on the front for ease of installation.
- Immersed adjustable Honeywell<sup>®</sup> aquastat for automatic temperature control.
- First hour deliveries ranging from 255 gallons to 325 gallons.
- Continuous hot water (135°F) supply of 235 gallons/hr at 180°F boiler supply and 157,000 BTU/hr. boiler input.
- I=B=R certification from the Hydronics Institute of GAMA.
- Limited Lifetime Warranty for tank and heat exchanger.

  
**BRADFORD WHITE**  
WATER HEATERS

[www.bradfordwhite.com](http://www.bradfordwhite.com)  
Ambler, PA | 800 523 2931

**Built to be the Best<sup>™</sup>**

©2008, Bradford White Corporation. All rights reserved.  
PWRSTMP-09/08

An energy saving indirect water heater  
with incredible output and efficiency!